


Overview Neon Glow-lamps 6x10mm



| priority type | Size | Lamp Type | Current [mA] | Striking Voltage AC (Vs) [V] | Striking Voltage DC [V] | Series Resistor (0,25W) 115V~ [Ohm] | Series Resistor (0,25W) 230V~ [Ohm] | Brightness | Average Live [h] | description |
|---------------|----------|-------------|--------------|------------------------------|-------------------------|-------------------------------------|-------------------------------------|-------------|------------------|--|
| X | 6x10,5mm | 610/30SB | 0,35-0,6 | 65 | 90 | 100-180k | 270K | Standart | 25K+ | Traditional type standard-brightness neon lamp with low strike-voltage (65V) suitable for all applications and for both 110V & 230V mains-voltage, low (0.50mA) operating-current, stable with uniform glow & 100% flicker-free, long live |
| X | 6x10,5mm | 610/30MB | 0,6 | 65 | 90 | 100K | 220K | Medium | 25K | Traditional type medium-brightness neon lamp with low strike-voltage (65V) suitable for all applications and for both 110V & 230V mains-voltage, low (0.60mA) operating-current, stable with uniform glow & 100% flicker-free, long live |
| X | 6x10,5mm | 610/30HB | 1 | 95 | 135 | 47K | 150K | Hight | 25K | Traditional High-brightness neon-lamp, high strike-voltage (95V) with high (1mA) operating-current. Rather unstable with initial non-uniform glow and with occasional flicker. |
| X | 6x10,5mm | 610/30HB-1 | 0,7-0,9 | 65 | | 68-82K | 180-270K | Hight | 25K+ | Improved type, medium-brightness neon-lamp, improved over traditional standard-brightness type neon-lamp with low strike-voltage (65V) suitable for all applications and for both 110V & 230V mains-voltage, medium-low (0.70mA) operating-current, stable with |
| | 6x10,5mm | 610/30HB-1X | 1,15 | 65 | | 47K | 150K | Hight | 20K | Modern improved type medium-brightness neon-lamp with low strike-voltage (65V) medium (1.05mA) operating-current, suitable for all applications and for both 110V & 230V mains-voltage, stable with uniform glow and 100% flicker-free. |
| | 6x10,5mm | 610/30UHB | 2,2 | 95 | 135 | 22K | 68K | Ultra Hight | 25K | Ultra High-brightness, high strike-voltage (95V) extra high operating-current (2.2mA), unstable with non-uniform initial glow and with occasional flicker. |
| X | 6x10,5mm | 610/30G/G | 0,8 | 80 | 120 | 68K | 180K | Green | 25K | Traditional type standard-brightness green fluorescent lamp with low strike-voltage (85V) suitable for all applications and for both 110V & 230V mains-voltage, low (0.25mA) operating-current, stable with uniform glow & 100% flicker-free, long live |
| | 6x10,5mm | 610/30G/R | 0,8 | 80 | 120 | 68K | 180K | Green | 25K | Traditional type standard-brightness green fluorescent lamp with low strike-voltage (85V) suitable for all applications and for both 110V & 230V mains-voltage, low (0.25mA) operating-current, stable with uniform glow & 100% flicker-free, long live, from topside red! |